

Predator Winter

SELECT LEATHER MECHANICS



PERFORMANCE STANDARDS

EN388



2122



CERTIFICATION



NB2056
CEC40300



FEATURES

- ▶ Only premium hides are selected and used in this glove to ensure the most soft and supple finish possible
- ▶ 4 Way Spandex is used in this glove construction allowing complete hand movement and flexibility
- ▶ 3M 100gsm breathable Thinsulate winter lining is used to keep hands warm from extreme cold
- ▶ Perfect form, fit and comfort is achieved through Force360's unique knit pattern that mimics a 'hand at rest', minimizing hand fatigue
- ▶ Only selected materials that allow air flow are used to ensure 360 degree air circulation and enhanced breathability
- ▶ UPF50+ offering maximum sun protection
- ▶ Reinforced double stitching for increased durability
- ▶ The Velcro closure allows the glove to be securely fastened ensuring a snug fit that reduces glove movement on the hand
- ▶ The ID area allows the wearer to mark their gloves with their name for easy ownership recognition or add an issue date for usage monitoring

INDUSTRIES

- ▶ Snowfields
- ▶ Refrigerated warehousing
- ▶ Gardening
- ▶ Maintenance
- ▶ Shipping
- ▶ Logistics & warehousing

SPECIFICATIONS

PART NO. GFPRMX12
LINER Leather

SIZING & FIT

AVAILABLE SIZES
M/8, L/9, XL/10, 2XL/11

DEXTERITY LEVEL

Maximum Dexterity Level 5
Certified under AS/NZS 2161.2

PACKAGING

1 pair per hang cell
12 pairs per inner pack
72 pairs per carton

REACH COMPLIANCE

Required Safe pH Level
Certified under AS/NZS 2161.2

AZO Dye and Irritant Chemical Free
Certified under AS/NZS 2161.2

SUN PROTECTION

UPF50+ Sun Protection
Pass under AS/NZS 4399 Sun Protective Clothing.
Tested by Australian Radiation Protection And Nuclear Safety Agency (ARPANSA).

GLOVE CARE

Cold hand wash only
Drip dry

KEY TECHNOLOGIES



SELECT LEATHER

Only premium hides are selected and used in this glove to ensure the most soft and supple finish possible.



4 WAY SPANDEX

Force360 only uses 4 Way Spandex in its glove construction allowing complete hand movement and flexibility.



3M THINSULATE LINED

3M 100 gsm breathable Thinsulate winter lining is used to keep hands warm from extreme cold.



REINFORCED WEAR POINTS

Force360 gloves last longer due to a double layer fabric coupled with double stitching reinforcement in high wear areas.



360 BREATHABILITY

Keeping hands cool is critical for comfort and improved wearer compliance. Only selected materials that allow air flow are used to ensure 360 degree air circulation and enhanced breathability.

WHY CERTIFY A GLOVES MECHANICAL SCORES?

Unknown to most people, gloves in Australia are almost always sold as compliant to European Standards. They will show a European Standards mark and mechanical score for example -'EN388 4542X'. They may state in their literature 'Compliant to European Standards' or 'meets European Standards'.

This is NOT the same as being certified to European Standards.

Compliant gloves can be simply marked with a particular cut level score of 5 or F for example; and the wearer must accept this claim. No further proof or validation from the glove manufacturer is required. For Force360 this is not acceptable. Hand injuries are commonplace and simply making compliance claims is just not enough to guarantee a glove's mechanical score, or it's protection level.

Asking a trusted and independent notifying body to certify the mechanical scores, guarantees that the scores are accurate and performance will meet this certification.

Force360 has entrusted **SAI Global**, the worlds' leading Standards Certifier to ensure that all mechanical scores are validated. This certification process ensures manufacturing processes and facilities, test certificates, and the product itself are audited & scrutinized so that all claims are accurate. The notifying body in affect becomes a gatekeeper of hand protection for the wearer.

Force360's entire hand protection range is certified by SAI Global to the latest European and Australian Standards.

Certified products must show a license number issued by the notifying body in addition to the EN388 mechanical scores.

